SC MIRAD TEHNIC SRL
Fixari si etansari in constructii
RO 19181471 : J22/2761/2006
IASI, STR. MARGARETA BACIU 11
RO37 RZBR 0000 0600 0852 4572
RAIFFEISEN BANK IASI

DECLARATIE DE CONFORMITATE

Noi, SC MIRAD TEHNIC SRL, cu sediul in Iasi, str. MARGARETA BACIU NR 11, certificate de inregistrare la registrul comertului J22/2761/2006, cod fiscal RO 19181471, asiguram, garantam si declaram pe proprie raspundere, conform art. 5 din HG1022/2002 ca produsele/serviciile livrate, conform facturii....., la care se refera aceasta declaratie, nu pun in pericol viata, sanatatea, securitatea muncii si protectia mediului si sunt in conformitate cu certificatele de conformitate si calitate emise de producator, respectiv importatorsi cu documentatia tehnica conform DIN (German Industrial Standard) 52210

Termenul de garantie este de 6 luni de la data livrarii, in conditiile manipularii , depozitarii si utilizarii normale.

Prezentul certificat atesta legal indeplinirea conditiilorde calitate si incadrarea inparametrii proiectati si solicitati.

BANDA PE LATIME/GROSIME MM **MIRAD 111**

Material and properties:	polyethylene-foam with closed cells, one-side self adhesive, **adhesive side not protected for quick mounting**
Field of application:	for acoustic sealing when mounting interior . The MIRAD partition-wall-tape is distinguished with very good insulation joint-sound-proof-measure $R_{ST,W}$ = 59 dB according to DIN (German Industrial Standard) 52210 High-grade pressure-sensitive adhesive – the applicability is even guaranteed at inferior temperatures
Colour:	black
Fire performance:	B1 according DIN 4102 –hardly inflammable- with building supervision approval P-MPA-E-01-635

Mirad Tehnic srl **Data.....**
Adrian Miron

SC MIRAD TEHNIC SRL
Fixari si etansari in constructii
RO 19181471 : J22/2761/2006
IASI, STR. MARGARETA BACIU 11
RO37 RZBR 0000 0600 0852 4572
RAIFFEISEN BANK IASI

Product Information PE 111

Description :

PE 111 consists of an one-sided self-adhesive closed-cell polyethylene foam.
The laminated PE film on the non-adhesive side allows a quick application without removal of a liner.

Application

The product is used as sealant. The special design of this tape allows a quick application without problems.

Product Properties

carrier	closed-cell polyethylene foam
adhesive	synthetic rubber
reinforcement	siliconised PE film, clear
liner	without
colour	black and white
density (ISO 845)	33 kg/m³
compressive strength at(ISO 844)	10 % 19 kPa
	25 % 38 kPa
	50 % 105 kPa
compression set 22 h at +23 °C and 25 % deforming (ISO 1856)	0.5 h after discharge 20 %
	24 h after discharge 10 %
thermal conductivity at +10 °C (ISO 8302)	0.034 W/m·K
temperature resistance	-40 °C bis +50 °C
compatibility with plexiglass	good

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage

6 month after receipt of goods, when stored at 18 °C and 60 % relative and Shelf Live humidity out of directsunlight, in original packaging

Special Information All data and technical information presented are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given.
You are kindly requested to conduct your own tests to determine the suitabilityof our product for your applications. Our General
Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations appl