BS 4,8 (FM approval)



Drill point screw

- For use in Steel deck from 0,70 mm up to 2x 1,25 mm
- For use with BIT-T25
- Torx-25 head
- Ø 4,8 mm
- Reduced drill point
- Lenght: from 50 to 300 mm
- Required length: Build up + 20 mm
- Enduroguard coating, 15 cycles
- Sintef technical approval 2516
- ETA approval 08/0285
- FM approval ID-Nr.3034551
  Read more about FM approvals

PRODUCT CODE	Ø MM x LENGTH MM	PACKAGING
1411758	BS-48050 4,8 x 50	1000
1411759	BS-48060 4,8 x 60	1000
1411760	BS-48070 4,8 x 70	1000
1411761	BS-48080 4,8 x 80	500
1411762	BS-48090 4,8 x 90	500
1413027	BS-48100 4,8 x 100	500
1413028	BS-48110 4,8 x 110	500
1413029	BS-48120 4,8 x 120	500
1413030	BS-48130 4,8 x 130	500
1413031	BS-48140 4,8 x 140	500
1413032	BS-48150 4,8 x 150	500
1413033	BS-48170 4,8 x 170	500
1413034	BS-48190 4,8 x 190	500
1413035	BS-48200 4,8 x 200	500
1413036	BS-48220 4,8 x 220	500
1413037	BS-48240 4,8 x 240	500
1413038	BS-48260 4,8 x 260	500
1413039	BS-48280 4,8 x 280	500
1413040	BS-48300 4,8 x 300	500