DBTA 4,8 (FM approval)



Drill point screw step secure

- For use in Steel deck form 0,70 mm up to 2x 1,25 mm
- For use with fully automatic tool IF 240
- 8mm hexagonal head
- Ø 4,8 mm
- Thread under head for step security
- Reduced drill point
- Length: from 60 to 220 mm
- Required length: Build up + 20 mm
- Enduroguard coating, 15 cycles
- Sintef technical approval 2516
- ETA approval 08/0285
- FM approval ID-Nr.3034551
  Read more about FM approvals

PRODUCT CODE	Ø MM X LENGTH MM	PACKAGING
BELTED FOR FULLY AUTOMATIC TOOLS		
1413064	DBTA-48060, 4,8 X 060	1200
1413066	DBTA-48080, 4,8 X 080	1200
1413068	DBTA-48100, 4,8 X 100	1050
1413069	DBTA-48120, 4,8 X 120	1050
1413070	DBTA-48140, 4,8 X 140	1050
1413071	DBTA-48160, 4,8 X 160	750
1413072	DBTA-48180, 4,8 X 180	750
1413073	DBTA-48200, 4,8 X 200	750
1413074	DBTA-48220, 4,8 X 220	750
1411884	DBTA-48240, 4,8 x 240	750