

## GS-TU



## PRODUCT DESCRIPTION

- Adjustable roof hook for universal roof tile. Stainless steel A2

## CHARACTERISTICS

- Pre-assembled product.
- Includes AISI-304 brackets.
- Includes two DIN-6923 nuts and two DIN-603 M10 bolts in A2-70 stainless steel.
- For outside use.
- For tiled roofs.
- Height-adjustable. For use under and on tiling.
- Three transversal mounting position options.
- Includes groove to facilitate adjustment.
- Includes nine drilled holes.
- Set up for mounting on the lower part of the tiling.
- Avoids the need to drill through tiling.
- Special design for mixed tiles.

## APPLICATIONS/MOUNTING ACCESSORIES



PSE-A



KFSFIM08



GP-XS



D603I08016 + D6923IM08


Used in **coplanar aluminium installation systems** to attach the systems to tiled roof sub-structures. When mounting the **PSE-A** "aluminium profile for assembled fixing", a **KFSFIM08** "cross connector for bottom fixing" is used on each roof hook.

Used in **coplanar Atlantis steel systems** to attach the systems to tiled roof sub-structures. When mounting **GP-XS** "INDEXTRUT solar perforated guide", one **D603I08016** "16 mm DIN-603 M8 bolt" and one **D6923IM08** "DIN-6923 M8 nut", both in A2-70 stainless steel, are used on each roof hook.


## ROOF/SUB-STRUCTURE/FIXING

ROOF	SUB-STRUCTURE BASE MATERIAL	FIXING
	WOOD	 TP A2 Countersunk head chipboard screw, A2 Stainless steel
	CONCRETE	
	HOLLOW CONCRETE	
	HOLLOW BRICK	 DIN-571 A2 Coach wood screw with hexagonal head, A2 Stainless steel
		 TN4S 4-way expansion nylon plug

## APPLICATION EXAMPLES



Application example 1: PSE-A profile mounting on concrete roof



Application example 2: Mounting of GP-XS perforated guide on concrete roof


## 1. RANGE

ITEM	CODE	PHOTO	DESCRIPTION	ADJUSTABLE HEIGHT	MATERIAL
1	GSTU040055		Adjustable roof hook for universal roof tile. Stainless steel A2	40 - 55 mm	 AISI-304

## 2. INSTALLATION INFORMATION

### 2.1 GS-TU


### Adjustable roof hooks for universal roof tile. Stainless steel A2

Material	Compatible	Mounting accessories	Roof
 AISI-304	 PSE-A Aluminium profile for assembled fixing	 KFSFIM08 Cross connector for bottom fixing	 Tile
	 GP-XS INDEXTRUT solar perforated guide	 D603I08016 + D6923IM08 DIN-603 M8x16 + DIN-6923 M8	
<b>Sub-structure base material</b>			<b>Fixing accessories</b>
 Wood			 TP A2 Countersunk head chipboard screw, A2 Stainless steel
 Concrete	 Hollow concrete	 Hollow brick	 DIN-571 A2 Coach wood screw w/ hexagonal head, A2 Stainless steel
		 Thermo-clay	 TN4S 4-way expansion nylon plug

#### Measurement table

Code	H1 (mm)	H2 (mm)	H (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E1 (mm)	E2 (mm)	E3 (mm)	F (mm)	G (mm)
GSTU040055	40-55	50-80	110-155	30	140	56	191	5	5	5	80	55

#### Drawing



#### Installation table

	Height adjustment			Profile fixing			Compression		Tensile	
	Nut	Height adjustment wrench (mm)	Max. installation tightening torque (N/m)	Nut	Installation wrench (mm)	Max. installation tightening torque (N/m)	Design load (kN)	Design load (kN)		
GSTU040055	M10	SW15	28	M8	SW13	14	0.4	0.4		